

**CLEAN COPY OF THE SUBSTITUTE SPECIFICATION**

**Title of the Invention**

**APPARATUS AND METHOD FOR PARTITIONING  
AND MANAGING SUBSYSTEM LOGICS**

**Inventors**

**Akinobu SHIMADA  
Hideo TABUCHI  
Yasuaki NAKAMURA  
Kozue FUJII  
Shotaro OHNO**

APPARATUS AND METHOD FOR PARTITIONING  
AND MANAGING SUBSYSTEM LOGICS

CROSS-REFERENCE TO RELATED APPLICATION

Japanese Patent Application No. 2003-300363

5 on which the present application is based and which was  
applied on Aug. 25, 2003 is herein incorporated by  
reference.

BACKGROUND OF THE INVENTION

Field of the Invention

10 The present invention relates to an  
apparatus, method, and program for partitioning and  
managing logics which are present in a subsystem, and a  
recording medium for recording the program.

Description of the Related Art

15 A storage subsystem is proposed which is  
expected to be accessed from a variety of types of  
computers and which has a port to which an interface  
for connecting to a plurality of computers can be  
applied, a logical unit (LU) which can be accessed from  
20 the computers via said port, one or a plurality of  
storage devices for storing data which is stored in  
said logical unit, and a storage control device for  
conducting read/write control on the storage devices in  
order to realize security for each logical unit while

effectively utilizing system resources in a conventional Logical Unit Number (LUN) security function. The computers accessing the logical unit are grouped into groups in such a manner that the computers  
5 can overlap each other. Each of the groups is assigned one or a plurality of logical units, and a management table is provided which correlates the assigned logical units and storage regions of the storage devices in such a manner that they can overlap each other.

10 On the other hand, the increasing storage capacity of a storage system has prompted large-scale storage consolidation. With storage consolidation, in a subsystem, there exist in a mixed manner a plurality of data belonging to a plurality of  
15 systems/applications. However, a security function in an aspect of storage management involved in storage consolidation has not sufficiently been provided by a GUI-level masking technology or conventional technology that provides security functions for data access  
20 itself.

That is, according to the conventional GUI-level masking etc., resources of upper storage management software are not partitioned on an interface which is adapted to instruct an actual storage to  
25 change a configuration. This is a problem. Therefore, such an issue is left unsolved that by using this interface, the configuration can be changed arbitrarily irrespective of a partitioning unit on a GUI etc.

Further, conventionally, partitioning of resources to such an extent that the upper storage management software can recognize (at a logical-volume level) is possible, whereas partitioning of physical resources that cannot be recognized by the management software (e.g., at an HDD level) has been impossible. Furthermore, even in the case of this partitioning at the logical-volume level, it cannot be known to which physical resources the logical volumes are allocated, so that some of the resources, even if partitioned as described above, may be common physically in some cases, which remains as a problem in performance or security.

Therefore, in a case where partitioning of logics of a subsystem in which storage consolidation has been performed is managed according to the conventional method, there is a possibility that an administrator may mistakenly perform an operation such as addition/deletion even to a region of other users, administrators and companies in relation to processing such as addition/deletion because such processing can be performed on an LU by configuration changing functions of an RAID. This may lead to system panic or user data destruction.

## SUMMARY OF THE INVENTION

Therefore, to accommodate storage consolidation and allow some of the configuration

changing functions of an RAID for multiple administrators, in view of the above problems, the storage system and the storage management software need to have a function to guard against configuration

5 changing of unauthorized area system area from an administrator other than the system area which is assigned for the administrator.

In view of such a background, the present invention has been made and it is an object of the

10 present invention to provide a subsystem logics partitioning and managing apparatus, method, and program for enabling configuration changing functions of an RAID within a predetermined limit, and a recording medium for recording the program.

15 For this end, a subsystem logics partitioning and managing apparatus according to one feature of the present invention comprises:

means for recognizing logical resources and physical resources that constitute a subsystem;

20 a partition definition table in which logical and physical resources in said subsystem are assigned for each user at an interface level at which a storage configuration can be referenced by a storage management program;

25 an account table in which a partition-specific account is set for each user defined in said partition definition table;

means for receiving a user account

transmitted from an information processing unit and collating the received user account to said account table to thereby recognize a partition corresponding to said user; and

- 5                   means for outputting logical resources and physical resources that are included in said recognized partition to an output interface as a resource configuration in said subsystem.

                  The subsystem logics partitioning and  
10 managing apparatus comprises means for outputting, at a GUI level, logical resources and physical resources that are contained in said partition to an output interface as a resource configuration in said subsystem.

                  The subsystem logics partitioning and  
15 managing apparatus comprises means for accepting from the information processing unit a request for changing a configuration of said output logical resources or physical resources and changing said configuration of said logical resources or said physical resources in  
20 said partition definition table.

                  Resources to be assigned for each user in said partition definition table include a port, a logical unit, a logical device indicative of a logical storage region assigned to said logical unit, and a  
25 disk unit group having a disk unit and a parity bit-use disk unit which stores data recovery information of said disk unit.

                  The subsystem logics partitioning and

managing apparatus comprises means for collating a requested specification of a logical unit accepted from an information processing unit to an assignment policy for said logical device and said disk unit group that  
5 are defined for each user, to perform assignment of a logical device and a disk unit group in accordance with said policy, thereby generating a logical unit.

The assignment policy comprises:

a first policy for selecting said logical  
10 device from a disk unit group to which no other partitions are assigned and in which no such disk unit group is present that control on input/output operations to disk units is conducted via the same adapter, to generate a logical unit;

15 a second policy for selecting said logical device from a disk unit group to which no other partitions are assigned, to generate a logical unit; and

a third policy for selecting said logical  
20 device from a disk unit group to which no other partitions that correspond to said first and second policies are assigned, to generate a logical unit.

Furthermore, resources to be assigned for each user include a cache.

25 According to another feature of the present invention there is provided a method for partitioning and managing logics in a subsystem which comprises a partition definition table in which logical resources

and physical resources in said subsystem are assigned for each user at an interface level at which a computer can reference a storage configuration by using a storage management program and an account table in  
5 which a partition-specific account is set for each user that is defined in said partition definition table, said method comprising the steps of:

recognizing said logical and physical resources that constitute said subsystem;  
10 receiving an account of a user transmitted from an information-processing device and collating the received user account to said account table, to recognize a partition corresponding to said user; and  
outputting logical and physical resources  
15 contained in said recognized partition to an output interface as a resource configuration in said subsystem.

According to a further feature of the present invention there is provided a subsystem logics  
20 partitioning and managing program for causing a computer capable of utilizing a partition definition table in which logical resources and physical resources in a subsystem are assigned for each user at an interface level at which a storage configuration can be  
25 referenced by using a storage management program and an account table in which a partition-specific account is set for each user that is defined in said partition definition table to perform a method for partitioning



and managing logics of said subsystem, said program comprising the steps of:

recognizing said logical and physical resources that constitute said subsystem;

5 receiving an account of a user transmitted from an information-processing device and collating the received user account to against said account table, to recognize a partition corresponding to said user; and

outputting logical and physical resources  
10 contained in said recognized partition to an output interface as a resource configuration in said subsystem. This program is comprised of codes for performing said steps.

According to a still further feature of the  
15 present invention there is provided a computer-readable recording medium for recording said subsystem logics partitioning and managing program.

The other problems and the corresponding solutions disclosed in the present application will be  
20 made clear by description of embodiments of the present invention and drawings.

According to the present invention, the configuration changing functions of the RAID can be released within a predetermined range.

## 25 BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features and advantages of the present invention will now become apparent from the

description of the embodiments of the invention in conjunction with the accompanying drawings.

FIG. 1 is an illustration for showing a configuration of a storage system according to an  
5 embodiment of the present invention.

FIG. 2 is an illustration for showing a use case image according to the present embodiment.

FIG. 3A is an illustration for showing a relationship among a disk array device, an API, and a  
10 GUI according to a conventional example.

FIG. 3B is an illustration for showing the relationship among a disk array device, an API, and a GUI according to the present embodiment.

FIG. 4 is a flowchart for showing an initial  
15 partition definition flow (with a policy) according to the present embodiment.

FIG. 5 is a flowchart for showing the initial partition definition flow (without policy) according to the present embodiment.

20 FIG. 6 is a flowchart for showing a configuration referencing/updating flow according to the present embodiment.

FIG. 7 is an illustration for showing a system configuration (with a policy base resource  
25 assigning function) and a partition definition table.

FIG. 8 is an illustration for showing the system configuration (without policy base resource assigning function) and the partition definition table.

FIG. 9 is an illustration for showing one example of an account table.

#### DETAILED DESCRIPTION OF THE EMBODIMENTS

##### <System Configuration>

5               FIG. 1 shows a configuration of a storage system according to the present embodiment. A subsystem 10 and a host 25 are interconnected via an interface 30 (hereinafter referred to as fibre channel 30) such as, for example, an SCSI or a fibre channel.

10 As one example of an information processing unit, the host 25 is, for example, an open-system type computer and can be assumed to be a personal computer or workstation in which an open-system type operating system (OS) operates. The subsystem 10 comprises a

15 plurality of ports 11 for connection with ports of the fibre channel 30, a channel adapter (CHA) 12 for controlling a cache and data transfer, a service processor 13 (here referred to as SVP), a shared memory 14 for storing configuration information for use in

20 control, a disk adapter (here referred to as DKA) 15 for controlling input/output operations to be performed to a storage device 16 such as an HDD, and the storage device 16.

              Further, as described above, not in a

25 physical configuration but in a logical configuration, the subsystem 10 comprises the ports 11, a host group 18 (here referred to as Host Group) assigned to the

port 11, a logical unit 19 (hereinafter referred to as LU), a logical device 20 (hereinafter referred to as LDEV), and a disk unit group 21 (here referred to as ECC Group).

5                   It is to be noted that a storage region of the storage system which is provided to the LU19 is managed in units of the LDEV20 (Logical Device). The LDEV20 is a logical volume includes a part of some disk units that compose a disk unit group of the disk array.

10   The host 25 specifies storage regions to be provided by the LDEV20, in units of said LU19. The LUs19 are each given a Logical Unit Number (LUN), which is a unique identifier. At the host 25, the LUN can be, for example, a drive name or a device file name.

15                   Further, said disk unit group 21 is comprised of a disk unit and a parity bit-use disk unit for storing data recovery information of this disk unit, which disk unit group 21 itself constitutes the LDEV20.

                  A management client 40 performs input/output

20   operations to this subsystem 10 through a network 35 such as an LAN and performs management processing. This management client 40 may be referred to as an input interface that permits an administrator (hereinafter referred to as user) of logical/physical

25   resources in the subsystem 10 which are partitioned and managed by a method according to the present invention to reference a configuration of these resources or request for changing the configuration. This

management client 40 can have access through the network 35 to a managing configuration information (partition definition table) 17 of the service processor 13, and reference only a configuration region of predetermined resources defined for the user and change it.

FIG. 2 is an illustration for showing a use case image according to the present embodiment. By applying a subsystem logics partitioning and managing method according to the present invention, even in the subsystem 10 in which a large-scale storage consolidation has been performed, data belonging to a plurality of systems/applications present in a mixed manner are partitioned for each of said users so that none of said users can violate a boundary between partitions.

That is, in contrast to, for example, a conventional GUI-level masking technique etc., resources of storage management software are partitioned on an interface provided for instructing an actual storage to change a configuration (which interface is supposed to be an application program interface (API)). Therefore, even if this interface is utilized to place access from the management client 40 to a partition 50 in the subsystem 10, no contradiction occurs between a partitioning unit returned from the service processor 13 to this management client 40 and a range within which the configuration can be changed.

For example, even if certain access to the partition 50 through the management client 40 is normal, access to any one of the other partitions 51-53 is not permitted. Further, GUI display about the other 5 partitions is not output. Alternatively, even if GUI display is given also about other partitions, changing etc. of the resource configuration is not accepted. In this case, a relationship among a display, the API, and the GUI is such as shown in FIG. 3. Partitioning 10 processing by the conventional technologies has been realized at a GUI level, to enable viewing or operating even a configuration of all of the resources at an API level. However, according to the present invention, the user is permitted to perform viewing or a variety 15 of operations only to a resource configuration at the GUI level, so that even a trial is made to view or change the resource configuration at, for example, the API level, only a configuration of the resources assigned to this user is presented from the beginning. 20 That is, partitioning is established even at the API level.

A storage manager managing the subsystem 10 integrally assigns the disk unit group 21 (in a logical configuration) that constitutes a partition for each of 25 said users from the disk unit group 21 (in a physical configuration) included in the subsystem 10. In this case, the service processor 13 can perform this processing by applying an internal hierarchy control

function (hereafter referred to as HIHSM) for moving/rearranging data to an optimal disk drive in accordance with access properties in the subsystem in which there are in a mixed manner a plurality of disk  
5 drives having different properties such as performance and a capacity.

Further, by applying a function (hereafter referred to as CVS) for creating a logical unit having an arbitrary size, a disk capacity can be utilized  
10 efficiently. Furthermore, by applying a function (hereafter referred to as LUSE) for combining a plurality of standard logical units to create a mass-capacity LU, it is possible to provide the logical unit  
19 having a huge size to the host, thus accommodating a  
15 large-scale application.

It is to be noted that by further applying a method according to the present invention to a subsystem to which conventionally proposed LUN security has been applied, in addition to a LUN security  
20 function for enabling setting an accessible host for each logical unit, such a function can also be provided as to correlate resource configuration display and a configuration changing permission/rejection scope for each of the users in the subsystem, which is  
25 preferable. Moreover, it is possible also to place access restrictions on a request for referencing/ changing of the resource configuration at an API level, thus further improving the security.

## &lt;Description of Processing&gt;

Description will be made of an actual procedure for performing subsystem logics partitioning and managing method according to an embodiment of the present invention. It is to be noted that various operations corresponding to the subsystem logics partitioning and managing method described below are realized by a program which is utilized by the service processor 14, which program is comprised of codes which are used to perform the various operations described below.

FIG. 4 is a flowchart for showing an initial partition definition flow (with a policy) according to an embodiment of the present embodiment. First, initial partitioning to be performed in response to a request sent from the user is described. The service processor 14 is supposed to have recognized logical and physical resources that constitute the subsystem 10, beforehand. Information of this configuration is stored in the managing configuration information 17 (s400). This configuration information 17 provides a definition table in which the logical resources and the physical resources in the subsystem are assigned for each of the users at an interface level at which a storage configuration can be referenced by the storage management program, that is, an API level.

In a partition definition table in FIG. 7



showing a system configuration (with a policy base resource assigning function) and the partition definition table, such a data configuration is provided that using a name of "User" as a key, IDs of a policy  
5 set about this user, and said port 11, host group 18, LVOL, LDEV20, and disk unit group (ECC) 21 that are assigned are related with columns 500-506 respectively.

When having received a user account transmitted as involved in access from an information  
10 processing unit such as said host 25 (s401), said service processor 14 collates the received user account to an account table (Fig. 9) for checking. FIG. 9 shows one example of an account table 600. The account table 600 has such a data configuration that using said  
15 name of "User" as a key, a user ID and a password are related with columns 601-603. These user ID and password can be registered only by an upper user (supervisor).

The service processor 14 can recognize or  
20 identify the partition 50 that corresponds to this user, based on said collation. For example, if the user name is "odawara", a configuration of accessible resources will be such that ports "1A" and "2A" correspond to host groups "00" and "00" respectively,  
25 with the LDEVs being "00.00" through "00.03", and the disk unit group being "1-1".

On the other hand, when having received a partition creation instruction containing instruction

information such as a port, a host group, an LVOL, or a policy from the user (s402), it collates a required specification of the logical unit 19 accepted from the information processing unit such as the host 25, with  
5 respect to an assignment policy for said logical device 19 and said disk unit group 21 that are defined for each of the users. FIG. 7 is an illustration for showing a system configuration (with a policy base resource assigning function) and a partition definition  
10 table. In this case, as shown in FIG. 7, said assignment policy is supposed to have been defined for each of the users in the managing configuration information 17.

Therefore, the managing configuration  
15 information 17 in the present embodiment has such a data configuration that using "User" as a key, the assignment policy, the port, the host group, the LVOL (virtual unit that corresponds to the required specification request), the LDEV, and the disk unit  
20 group are related with the columns 500-506. However, until the LVOL that corresponds to said use request is defined, said LDEV and said disk unit groups remain undefined.

The service processor 14 recognizes this  
25 policy based on said managing configuration information 17 (s403). If the user is, for example, "odawara", the relevant assignment policy is "independent" (written as "independent"). This "independent" policy provides a

first policy that gives a provision to the effect that "a logical unit should be generated by selecting a logical device from a disk unit group to which no other partitions are assigned and in which no such disk unit group is present that control on input/output operations to disk units is conducted via the same adapter".

Further, as an example of the other policies, there is a second policy, that is, "partially shared" policy (hereafter referred to as "partial") that gives a provision to the effect that "a logical unit should be generated by selecting said logical device from a disk unit group to which no other partitions are assigned".

Furthermore, there is a third policy, that is, "shared use" policy (hereafter referred to as "shared") that gives a provision to the effect that "a logical unit should be generated by selecting said logical device from a disk unit group to which no other partitions corresponding to said first and second policies are assigned".

The service processor 14, which has recognized the assignment policy as described above, performs assignment of a logical device and a disk unit group that correspond to this policy (s404). Based on these selected logical device and disk unit group, it generates a logical unit (s405). Now that the logical unit has been thus generated and so the resource

configuration of this user's partition has been updated, of course said managing configuration information 17 is also updated. That is, the process registers the resources in the partition definition  
5 table (s406) and ends the processing.

FIG. 5 is a flowchart for showing the initial partition definition flow (without policy) according to the present embodiment. Next, initial partitioning processing in response to a request from the user in  
10 the case of taking into account no policy is described. The service processor 14 is supposed to have recognized beforehand the logical and physical resources that constitute the subsystem 10. Information of this configuration is stored in the managing configuration  
15 information 17 beforehand (s500). This managing configuration information 17 provides a definition table in which the logical resources and the physical resources in the subsystem are assigned for each of the users at an interface level at which the storage  
20 configuration can be referenced by the storage management program, that is, an API level.

In a partition definition table in FIG. 8 showing the system configuration (without policy base resource assigning function) and the partition  
25 definition table, such a data configuration is provided that using a name of "User" as a key, IDs of said port 11, host group 18, LDEV20, and disk unit group (ECC) 21 that are assigned to this user are related to columns

400-404.

When having received a user account transmitted as involved in access from an information processing unit such as said host 25 (s501), said  
5 service processor 14 collates the received user account against the account table (see FIG. 9) the same way as described above.

The service processor 14 can recognize the partition 50 that corresponds to this user, based on  
10 said collation. For example, if the user name is "odawara", a configuration of accessible resources will be such that ports "1A" and "2A" correspond to host groups "00" and "00" respectively, with the LDEVs being "00.00" through "00.03", and the disk unit group being  
15 "1-1".

On the other hand, when having received a partition creation instruction containing instruction information such as a port, a host group, or an LVOL from the user (s502), it collates a required  
20 specification of the logical unit 19 accepted from the information processing unit such as the host 25 against a situation, contained in the managing configuration information 17, in which said logical device 19 and said disk unit group 21 are assigned to the other  
25 users. As shown in FIG. 8, said managing configuration information 17 has such a data configuration that using "User" as a key, the assigned port, host group, LDEV, and disk unit group are related with the columns 400-

404.

Said service processor 14, which has recognized the resources that can be assigned to said user based on said managing configuration information 5 17, assigns a logical device and a disk unit group (s503). Based on these selected logical device and disk unit group, it generates a logical unit (s504). Now that the logical unit has been thus generated and so the resource configuration of this user's partition 10 has been updated, of course said managing configuration information 17 is also updated.

That is, the process registers the resources in the partition definition table (s505) and ends the processing.

15               Next, resource configuration referencing/ updating to be performed in response to a request from the user is described. FIG. 6 is a flowchart for showing a configuration referencing/ updating flow according to the present embodiment. The service 20 processor 14 is supposed to have recognized beforehand the logical and physical resources that constitute the subsystem 10 (s600). Information of this configuration is stored in the managing configuration information 17 as described above.

25               The service processor 14 accepts from an information processing unit such as said host 25 a user's login request involving a specification of a user ID and a password and goes through appropriate

authentication processing, to perform login processing (s601). When having received a user account transmitted as involved in the login (s602), the service processor 14 collates it against an account  
5 table shown in FIG. 9 as described above.

The service processor 14 can recognize the partition 50 that corresponds to this user, based on said collation (s603). For example, if the user is "odawara", a configuration of accessible resources will  
10 be such that ports "1A" and "2A" correspond to host groups "00" and "00" respectively, with the host group being "00", the LDEVs being "00.00" through "00.03", and the disk unit group being "1-1" (see FIG. 7 or 8).

The service processor 14 outputs to said host  
15 25 the logical resources and the physical resources that are contained in said recognized partition 50, as a resource configuration in the subsystem (s604). If, then, no changing request is sent from the host 25 (NO at s605), the processing ends. If a changing request  
20 is sent from the host 25 (YES at s605), on the other hand, it is accepted (s606). In this case, of course, the other partitions or changing requests from the other partitions are rejected.

The service processor 14, which has received  
25 said changing request, allows rewriting of the relevant logical resources or physical resources in said managing configuration information 17. Alternatively, it changes contents of the table in order to change the

configuration in accordance with contents of the changing request (s607) and ends the processing.

It is to be noted that said service processor 14 can also output at a GUI level to said host 25 the logical resources and the physical resources that are contained in a partition 50 assigned for each user, as a resource configuration in the subsystem. It is to be noted that the resource configuration to be output at the GUI level is supposed to contain only such resources that a user's request for configuration changing/viewing can be accepted. Therefore, a request for changing/viewing about partitions of the other users or from the other partitions is rejected. Alternatively, such a configuration may be provided that only viewing is permitted but configuration changing is not accepted.

In said GUI output, such data may be assumed that a relationship among said resources is configured in a tree format. Further, a pattern of the GUI output may be any of a variety of applicable ones such as a pattern in which only the partition 50 of said user is displayed and the other partitions are masked, a pattern in which resources shared in the configuration, if any, are added to said partition 50 and displayed, and a pattern in which all the partitions are displayed but configuration changing of only the partition 50 is accepted.

Furthermore, displaying/masking of said



configuration resources may be subject to output processing based on a policy in said managing configuration information 17, in such a manner that if, for example, the policy is "independent", only the

5 configuration resources of the relevant user are displayed, that if the policy is "shared use", both the configuration resources of the relevant user and those of the other users are displayed, and that if it is "partially shared", engagement between the

10 configuration resources of the relevant user and those shared by him and the other users is also displayed.

As described above, the subsystem logics partitioning and managing method according to the present invention is performed for managing, at an API

15 level, access to a partition of interest from an information processing unit and changing of a configuration.

It is thus possible to release (some of) the configuration changing functions of the RAID while

20 keeping security, for each of the partitions 50, that is, for each system or each user of an application. That is, said user can perform addition/changing of settings of resources within a range of volumes assigned by a storage manager.

25 Such an effect becomes more significant especially in a situation that storages of a plurality of systems are present in a mixed manner in one subsystem owing to storage consolidation, thereby

providing a merit of integrated management due to storage consolidation without deteriorating convenience of each user.

Therefore, it is possible to provide a  
5 subsystem logics partitioning and managing apparatus, method, and program for enabling releasing configuration changing functions of the RAID within a predetermined range, and a recording medium for recording the program.

10 Although the present invention has been described with reference to its embodiments, the present invention is not limited to them but may be modified variously without departing from its gist in scope.